

TECHNICAL DATA SHEET

Gaia™ Antiskid Paper Sheets Roll Stock - Low GSM

Description

Two sides coated compostable paper-based antiskid sheets for catering trays and interleaving sheets based on FBC* solution, water and oil resistant. This product is recyclable and compostable (industrial). Can be supplied as 1-side coated.



Typical End Uses

Antiskid catering trays sheets & interleaving sheets.

* FBC stands for Functional Barrier Coating.

TYPICAL PROPERTIES

| Properties | Unit | Value | Method |
|----------------------|------|----------------------|-------------|
| Total Weight | GSM | 66 ± 5% to 100 ± 5% | ISO 536 |
| FBC Weight | GSM | 8 to 10 on each side | |
| Slide Angle | ° | 45 | ISO 535 |
| COF (C/C**) | N | > 0.45 | ISO 8295 |
| Dry Tensile Strength | MD | KN/m | ISO1924-3 |
| | CD | KN/m | |
| | | | 2.57 - 3.05 |

**Coated side

CONFORMITY WITH EU DIRECTIVES

The coated material complies with EC and FDA regulations; Food Compliance Certificate is available upon request.

STORAGE

The material should be stored at temperatures between 10 to 35 °C with relative humidity between 40 to 70%, in a clean and dust free environment.

The material should be conditioned 24 hours in the production area prior to use on the machine.

Use within one year from the production date.

Important: The information given is based on our knowledge and experience at the time of production and is given in good faith. It does not represent a guarantee or legal warranty for specific properties or for suitability for a specific use. The responsibility for testing the suitability of the product for the foreseen use lies with the purchaser. However, should there be cause for claim; liability is, in all cases, limited to the value of the goods supplied.

Address: Napco National, 1st Industrial Area, 3rd street, P.O .BOX 538, Dammam, Saudi Arabia
Tel: 00966138459400, Fax: 00966138471435, E-mail: info@napcopaper.com, website: www.napconational.com